





TYPE	EP2 (Efficiency & Power Two)														Approx Weight (kg)
GEAR RATIO	1/5	1/10	1/15	1/20	1/30	1/40	1/50	1/60	1/75	1/80	1/90	1/100	1/150	1/200	
RPM	360	180	120	90	60	45	36	30	24	22.5	20	18	12	9	



감속기 형번 (출력축)	THREE PHASE INDUCTION MOTOR SPEC										APPD BY	IL HWAN KIM	UNIT	mm	SUBJECT	EP2	Revision No.	0
	PH	P	kW	VOLTS	Hz	BEARING NO.	기동방식	절연종류	PRO- TEC- TION	RA- TING	CHKD BY	KEOAK HOON	SCALE	N/S	TITLE	OUT LINE		
											DSND BY	LEE EUN HWA	PROJEC'N	3rd Angle				
28	3	4	0.2	-	-	6203/6202	직입기동	B 종	IP44	CONT.	DATE	2015.10.06	PAGE		REF. NO	RATIO 1/5~1/200	DWG NO	H0280200T002A06
											 SNC SHINMYUNG ELECTRIC CO.,LTD							

TYPE	EP2 (Efficiency & Power Two)														Approx Weight (kg)
GEAR RATIO	1/5	1/10	1/15	1/20	1/30	1/40	1/50	1/60	1/75	1/80	1/90	1/100	1/150	1/200	
RPM	360	180	120	90	60	45	36	30	24	22.5	20	18	12	9	



감속기 형번 (출력축)	THREE PHASE INDUCTION MOTOR SPEC										APPD BY	IL HWAN KIM	UNIT	mm	SUBJECT	EP2	Revision No.	0
	PH	P	kW	VOLTS	Hz	BEARING NO.	기동방식	절연종류	PRO- TEC- TION	RA- TING	CHKD BY	KEOAK HOON	SCALE	N/S	TITLE	OUT LINE		
											DSND BY	LEE EUN HWA	PROJEC'N	3rd Angle				
28	3	4	0.2	—	—	6203/6202	직입기동	B 중	IP44	CONT.	DATE	2015.10.06	PAGE		REF. NO	RATIO 1/5~1/200	DWG NO	H0280200T002A08

